

B-Lok series 821-823

Applications: thermoplastic and fibrous materials.

Assembly: by pressure through expansion anchorage.







code	metric thread	external diameter	total length	number of vanes	diameter hole
	d1	d2	L	n°	d3
821 0030.80	M 3	5,35	4,8	1	4,5 ÷ 4,7
822 0040.80	M 4	6,65	9,5	2	5,8 ÷ 6,0
822 0050.80	M 5	7,35	9,5	2	6,5 ÷ 6,7
822 0060.80	M 6	9,05	9,5	2	8,2 ÷ 8,4
823 0080.80	M 8	12,5	14,3	3	11,8 ÷ 12,0

Non binding dimensions, expressed in mm.

For a correct usage of the product it is advisable to carry out some preliminary assembling tests to determine the correct hole diameter.

Standard

On demand

-- Not manufactured

Material: brass Finishing: natural Tolerances: ISO 2768 - m Threading d1: ISO 6 H metric

Example: insert B-lok, M5 thread, brass:

822 0050.80



/pecialin/ert

www.specialinsert.it - export@specialinsert.it

HEAD OFFICE:
10142 TORINO - strada della Pronda 66/6 - tel. +39 011700301 r. a. - fax +39 011702947
EXPORT BRANCH:
20161 MILANO - via E. Cialdini 37 - tel. +39 026468476 r. a. - fax +39 0266200275
BRANCH AND FACTORY:

30030 MAERNE DI MARTELLAGO (VE) via E. Pavanello n°1 - tel. +39 0415030100 r. a. fax +39 0415030110

SPECIALINSERT, COMMITS ITSELF TO CONTINUOUSLY IMPROVE ITS +
PRODUCTS IT RESERVES THE RIGHT TO CHANGE THER TECHNICAL
AND STRUCTURAL CHARACTERISTICS WITHOUT PRIOR NOTICE.
ALL RIGHTS ARE RESERVED AND THE DUPLICATE EVEN PARTIAL,
OF THESE DOCUMEN'S AS WELL AS ITS DISTRIBUTION TO THING PARTIES.
ARE FORBIDDEN, UNLESS OTHERWISE AND EXPRESSLY AUTHORIZED BY SPECIALINSERT.